

DUMPS ARENA

Zend Certified PHP Engineer

Zend 200-550

Version Demo

Total Demo Questions: 15

Total Premium Questions: 223

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

What is the recommended method of copying data between two opened files?

- A. `copy($source_file, $destination_file);`
- B. `copy($destination_file, $source_file);`
- C. `stream_copy_to_stream($source_file, $destination_file);`
- D. `stream_copy_to_stream($destination_file, $source_file);`
- E. `stream_bucket_prepend($source_file, $destination_file);`

ANSWER: C

QUESTION NO: 2

Which of the following PHP functions can be used to set the HTTP response code? (Choose 2)

- A. `header_add()`
- B. `header()`
- C. `http_set_status()`
- D. `http_response_code()`
- E. `http_header_set()`

ANSWER: B D

QUESTION NO: 3

Which of the following superglobals does not necessarily contain data from the client?

- A. `$_POST`
- B. `$_SESSION`
- C. `$_GET`
- D. `$_SERVER`

ANSWER: B**QUESTION NO: 4**

Which methods can be used to overload object properties? (Choose 2)

- A. set(), get()
- B. __set(), __get()
- C. __put(), __receive(), __exists()
- D. set(), get(), isset()
- E. __isset(), __unset()

ANSWER: B E**QUESTION NO: 5**

What is the output of the following code? class A { public \$a = 1;

```
public function __construct($a) { $this->a = $a; }
```

```
public function mul() { return function($x) {
```

```
return $this->a*$x;
```

```
};
```

```
}
```

```
}
```

```
$a = new A(2); $a->mul = function($x) {
```

```
return $x*$x;
```

```
};
```

```
$m = $a->mul(); echo $m(3);
```

- A. 9
- B. 6
- C. 0
- D. 3

ANSWER: B

QUESTION NO: 6

What will the following code print out? `$str = '✓ one of the following'; echo str_replace('✓', 'Check', $str);`

- A. Check one of the following
- B. one of the following
- C. ✓ one of the following

ANSWER: A

QUESTION NO: 7 - (SIMULATION)

SIMULATION

Your supervisor wants you to disallow PHP scripts to open remote HTTP and FTP resources using PHP's file functions. Which php.ini setting should you change accordingly?

ANSWER: allow_url_fopen -or- allow_url_fopen=off -or- allow_url_fopen=Off -orallow_url_fopen = off - or- allow_url_fopen = Off

QUESTION NO: 8

Which of the following functions will allow identifying unique values inside an array?

- A. array_unique_values
- B. array_distinct
- C. array_count_values
- D. array_intersect
- E. array_values

ANSWER: C

QUESTION NO: 9 - (SIMULATION)

SIMULATION

What is the name of the key for the element in `$_FILES['name']` that contains the provisional name of the uploaded file?

ANSWER: tmp_name

QUESTION NO: 10

What is the output of the following code?

```
class a
{
public $val;
}
function renderVal (a $a)
{
if ($a) { echo $a->val;
}
} renderVal (null);
```

- A. A syntax error in the function declaration line
- B. An error, because null is not an instance of 'a'
- C. Nothing, because a null value is being passed to renderVal()
- D. NULL

ANSWER: B

QUESTION NO: 11

Which of the following methods are available to limit the amount of resources available to PHP through php.ini? (Choose 2)

- A. Limit the amount of memory a script can consume
- B. Limit the total amount of memory PHP uses on the entire server
- C. Limit the maximum execution time of a script
- D. Limit the maximum number of concurrent PHP processes
- E. Limit the maximum number of concurrent PHP threads

ANSWER: A C

QUESTION NO: 12

After performing the following operations:

```
$a = array('a', 'b', 'c');
```

```
$a = array_keys(array_flip($a));
```

What will be the value of \$a?

- A. array('c', 'b', 'a')
- B. array(2, 1, 0)
- C. array('a', 'b', 'c')
- D. None of the above

ANSWER: C

QUESTION NO: 13

An unbuffered database query will: (Choose 2)

- A. Return the first data faster
- B. Return all data faster
- C. Free connection faster for others scripts to use
- D. Use less memory

ANSWER: A D

QUESTION NO: 14

When retrieving data from URLs, what are valid ways to make sure all file_get_contents calls send a certain user agent string? (Choose 2)

- A.

```
$default_opts = array('http'=>array('user_agent'=>"My Cool Browser"));  
$default = stream_context_set_default($default_opts);
```
- B.

```
stream_context_set_option("user_agent", "My Cool Browser");
```
- C.

```
ini_set('user_agent', "My Cool Browser");
```

D. `stream_context_set_option($context, "http", "user_agent", "My Cool Browser");`

ANSWER: A C

QUESTION NO: 15

Which function can NOT help prevent cross-site scripting? (Choose 2)

- A. `addslashes()`
- B. `htmlentities()`
- C. `htmlspecialchars()`
- D. `strip_tags()`
- E. `quotemeta()`

ANSWER: A E