

DUMPS ARENA

GIAC GIAC Secure Software Programmer - C#.NET

GIAC GSSP-NET-CSHARP

Version Demo

Total Demo Questions: 15

Total Premium Questions: 235

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

The U1900 has a CDR pool. If the network is disconnected, CDRs will be stored in the CDR pool of the U1900. When the network is recovered, the CDRs in the CDR pool will be pushed to the CDRServer.

- A. TRUE
- B. FALSE

ANSWER: A**QUESTION NO: 2**

Faxes can be sent and received through Internet in transparent transmission or T.38 mode. The difference is that faxes are transmitted as voice packets over Internet in transparent transmission mode while as data packets over Internet in T.38 mode.

- A. TRUE
- B. FALSE

ANSWER: A**QUESTION NO: 3**

Which of the following parameters must be set when you configure the ATO trunk on the U1900 series unified gateway?
(Multiple Choice)

- A. Port number
- B. Office route number
- C. Peer office IP address
- D. Line selection mode

ANSWER: A B D**QUESTION NO: 4**

Through the eSight version file management function, version files of IP phones can be updated and upgraded in batches.

- A. TRUE
- B. FALSE

ANSWER: A

QUESTION NO: 5

Which of the following intelligent routing policies are supported by U1900? (Multiple Choice)

- A. Rerouting upon a routing failure
- B. Routing by time segment
- C. Routing by VoIP domain
- D. Routing by trunk level

ANSWER: A B

QUESTION NO: 6

Company A plans to deploy the automatic switchboard service, through which users can dial the desired extension numbers or dial 0 to connect to the secretary deployment as prompted. The short numbers for company A's employees contain four digits, and the long numbers contain eight digits. To prevent toll fraud of external users, the length of the number dialed following the automatic switchboard number needs to be limited to () digits.

- A. 1
- B. 4
- C. 8
- D. 2

ANSWER: B

QUESTION NO: 7

eSpace U1960 can support () analog trunks at most.

- A. 12
- B. 72
- C. 84
- D. 100

ANSWER: B

QUESTION NO: 8

In U1900 series unified gateway, which of the following statements are CORRECT about the relationships among prefixes, office routes, office route selection codes, and trunks for eSpace U1900? (Multiple Choice)

- A. A prefix can map only one office route selection code.
- B. An office route selection code can map only one prefix.
- C. Office route selection codes and office routes have a one-to-many relationship.
- D. An office route can map the trunks of different types.

ANSWER: A D**QUESTION NO: 9**

Which of the following statements are CORRECT about the PRA protocol? (Multiple Choice)

- A. The protocol consists of the physical layer, data link layer, and network layer.
- B. The protocol is used for link multiplexing and error detection at the physical layer.
- C. The standard protocol used at the data link layer is Q.921.
- D. The standard protocol used at the network layer is Q.931.

ANSWER: A C D**QUESTION NO: 10**

On U1900 series unified gateways, which of the following outgoing call rights are available for users of the default level? (Multiple Choice)

- A. Intra-office call
- B. Local call
- C. National toll call
- D. International toll call

ANSWER: A B**QUESTION NO: 11**

The priority of the system blacklist and whitelist is lower than that of the personal blacklist and whitelist

- A. TRUE

B. FALSE

ANSWER: A

QUESTION NO: 12

Perform the following configurations on the U1960:

1. Create an office route selection code by setting Office route selection code to 8, Office route selection policy to None, and Failure Processing Index to None.
2. Create an office route by setting Office route number to 8 and Office route selection code to 8.
3. Create another office route by setting Office route number to 9 and Office route selection code to 8.
4. Create a prefix by setting Prefix to 9, Service type to Basic service, Call property to Local call. Called number change to None, and Office route selection code to 8.

According to the preceding configurations, which of the following statements is CORRECT? ()

- A. When a user views the office route mapping the office route selection code 8 on the U1960, only office route 9 exists, and office route 8 is replaced by office route 9.
- B. When a user on the U1960 dials prefix 9 to make an outgoing call, office route 9 is preferred to route the call.
- C. When a user on the U1960 dials prefix 9 to make an outgoing call, office route 8 is preferred to route the call.
- D. When a user on the U1960 dials prefix 9 to make an outgoing call, office route 9 is preferred to route the call. When the trunk for office route 9 is faulty, the call will be rejected.

ANSWER: C

QUESTION NO: 13

Which of the following statements are CORRECT? (Multiple Choice)

- A. The AT0 trunk is often used to implement DDI features.
- B. The SS7 trunk can be an ISUP trunk or a TUP trunk.
- C. The PRA can be configured at the user side or at the network side.
- D. SIP is a transport-layer control (signaling) protocol.

ANSWER: A B C

QUESTION NO: 14

The U1981 unified gateway supports () PRA trunk at most.

- A. 4
- B. 8
- C. 12
- D. 24

ANSWER: D

QUESTION NO: 15

Numbers have been allocated to SIP users on the U1900 series unified gateway. Numbers can be allocated to analog phones directly connected to the IAD only after () are configured on the IAD. (Multiple Choice)

- A. SIP server IP address
- B. FXS users
- C. FXO users
- D. SIP Trunk parameters

ANSWER: A B