

DUMPS ARENA

Hitachi Data Systems Certified Implementer – Enterprise exam

Hitachi HH0-210

Version Demo

Total Demo Questions: 10

Total Premium Questions: 120

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

Topic Break Down

Topic	No. of Questions
Topic 1, Volume A	59
Topic 2, Volume B	61
Total	120

QUESTION NO: 1

The SVP has failed on a VSP and you have ordered a replacement. Which functionality is still available while waiting for the new SVP to arrive on site?

- A. Configuration changes can be made using raidcom commands.
- B. Hitrack can continue monitoring the VSP and report errors.
- C. Configuration changes can be made using HiCommand CLI.
- D. ShadowImage pairs can be managed with RAID Manager/CCI.

ANSWER: D**QUESTION NO: 2**

What is Hitachi Data System's recommended practice for zoning?

port-based zoning zoning is optional

- C. single HBA zoning -- one HBA per zone
- D. single operation system zoning -- all HBAs from one OS in a zone

Answer: C

Explanation:

- A. single HBA zoning -- one HBA per zone
- B. single operation system zoning -- all HBAs from one OS in a zone

ANSWER: A**QUESTION NO: 3**

Which two statements about LU Size Expansion (LUSE) are true for a Hitachi VSP system? (Choose two.)

- A. LUSE volumes can reside on external storage.
- B. You can make a LUSE from LDEVs on different CUs.

- C. You can only make a LUSE when LDEVs are the same size.
- D. You can make a LUSE from LDEVs of different emulation type.

ANSWER: A B

QUESTION NO: 4

Which three steps should be performed during a new VSP installation? (Choose three.)

- A. Install HiTrack Monitor on a customer server and configure it.
- B. Set the battery date for each battery.
- C. Install all SSVP jumpers.
- D. Connect the CE laptop to the Console LAN connection port on the SVP.
- E. Dump the final configuration and upload it to TUF.

ANSWER: B D E

QUESTION NO: 5

Which three operations are allowed after activating LUN security on a VSP Fibre Channel (FC) port? (Choose three.)

- A. Add multiple WWNs to one Host Group.
- B. Add a LDEV to two different Host Groups on the same FC port.
- C. Create a Host Group with two different Host connection modes.
- D. Add the same WWN to two different Host Groups on the same FC port.
- E. Create host groups with different Host connection modes on the same FC port.

ANSWER: A B E

QUESTION NO: 6

Your customer wants to connect multiple servers with different operating systems to the same port on a VSP. What is the first step when configuring the port?

- A. Map a LUN.
- B. Register a WWPN.
- C. Enable Port Security.
- D. Create a Host Group.

ANSWER: C

QUESTION NO: 7

You need to install Hitachi Dynamic Link Manager (HDLM) on a Windows server. Which documentation provides detailed information about the supported Fibre Channel HBA drivers?

- A. HDLM HBA Guide
- B. HDLM Release Notes
- C. HDLM Concepts and Planning Guide
- D. HDLM for Windows Systems User's Guide

ANSWER: B

QUESTION NO: 8

Which two statements regarding how users login to Storage Navigator 2 on a VSP are correct? (Choose two.)

- A. user name can only be used by one user at a time.
- B. Multiple users can login using a different user name each.
- C. Multiple users can login using the same user name.
- D. A maximum of 4 users can login at the same time.

ANSWER: A B

QUESTION NO: 9

To what does the SSW HP0 of a VSP HDU box connect to?

- A. Cluster 1
- B. Cluster 2
- C. MPB
- D. HUBBOX

ANSWER: A

QUESTION NO: 10

You have replaced a part on a VSP. What are three mandatory steps to complete your maintenance task? (Choose three.)

- A. Complete the "Last maintenance" form inside the DKC door.
- B. Complete the corresponding SIM(s).
- C. Reboot the SVP to renew the configuration.
- D. Check the maintenance screen for any blinking parts.
- E. Set the SVP application back to View Mode.

ANSWER: B D E