

DUMPS ARENA

Hitachi Data Systems Storage Architect-Hitachi NAS Platform

Hitachi HH0-450

Version Demo

Total Demo Questions: 10

Total Premium Questions: 120

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

Topic Break Down

Topic	No. of Questions
Topic 1, Volume A	59
Topic 2, Volume B	61
Total	120

QUESTION NO: 1

A customer would like to implement network load balancing from a Hitachi NAS Platform node to a single Ethernet switch. Which network technology is required?

- A. Hot Standby Router (HSRP)
- B. Link Aggregation (LAG)
- C. Link Aggregation Control Protocol (LACP)
- D. MPIOX

ANSWER: B**QUESTION NO: 2**

The administrator of a production Hitachi NAS Platform 3200 wants to maximize potential performance and fault tolerance to an attached Hitachi USP V storage system. Which configuration should be used?

- A. Use hports 1, 2, 3 and 4 of the Hitachi NAS Platform to connect to different FED ports on cluster 1 of the USP V.
- B. Use hports 1, 2, 3 and 4 of the Hitachi NAS Platform to connect to FEDs on cluster 1 and cluster 2 of the USP V.
- C. Use hports 4, 5, 6 and 7 of the Hitachi NAS Platform to connect to different FED ports on cluster 1 of the USP V.
- D. Use hports 1, 3, 5 and 7 of the Hitachi NAS Platform to connect to FEDs on cluster 1 and cluster 2 on the USP V.

ANSWER: D**QUESTION NO: 3**

A customer has a Hitachi AMS2100 attached to a 2-node Hitachi NAS Platform 3090 cluster. They initially purchased 15 TB and have just purchased an additional 5 TB. They now need to expand their existing storage pools. What must be considered when expanding the storage pools?

- A. All system drives must be of the same size in terms of capacity.
- B. All system drives must be offline.
- C. All system drives must be in the same system drive group.

D. All storage pools must be offline.

ANSWER: A

QUESTION NO: 4

You are asked to design a Hitachi NAS Platform solution for a customer with existing Hitachi storage systems installed. The existing storage and SAN infrastructure should be used wherever possible. Which two can be re-used? (Choose two.)

- A. spare Qlogic 2310 HBAs
- B. Fibre Channel switches
- C. Hitachi AMS500 storage systems
- D. Hitachi 7700E storage systems

ANSWER: B C

QUESTION NO: 5

Your customer is planning a disaster recovery site and they need to know the form factors of the Hitachi NAS Platform models for physical planning purposes. Which two statements are correct ? (Choose two.)

- A. The 3090 fits into a 19 inch rack and is 3 rack units high.
- B. The 3080 fits into a 19 inch rack and is 2 rack units high.
- C. The 3200 fits into a 19 inch rack and is 4 rack units high.
- D. The 3090 and 3100 fit into a 19 inch rack and are of the same height.

ANSWER: A C

QUESTION NO: 6

A customer with a Hitachi NAS Platform connected to a production Hitachi USP V requires a Recovery Point Objective (RPO) of 20 minutes or less for their replicated data. Each of their four file systems has a minimum of 20 TB of data and 50 million files. Each file system has a heavy change rate. Which three replication products meet the customer's RPO?

(Choose three.)

- A. Hitachi Universal Replicator
- B. TrueCopy
- C. Intelligent Data Replication
- D. Incremental Block Replication
- E. ShadowImage

ANSWER: A B E

QUESTION NO: 7

A customer wants to implement a Hitachi NAS Platform 3200 in a 1 GbE network environment and they are asking about potential performance limiting factors in a network.

Which two factors should they take into consideration? (Choose two.)

- A. the use of a Network File System
- B. how ASICs are shared in a switch
- C. the number of modules (blades) in a switch
- D. the number of network hops

ANSWER: B D

QUESTION NO: 8

A customer is running Active Directory with Windows 2003 R2 and Windows 2008 servers acting as domain controllers. They also have a large UNIX environment. They would like to integrate a Hitachi NAS Platform using a centralized user and group mapping for their heterogenous environment. What should be done?

- A. Load the RFC 2307 Schema on the LDAP server.
- B. Downgrade all Windows servers to Windows 2000.
- C. Install NIS+ on all the UNIX servers.
- D. Enable SMTP for time synchronization between UNIX and Windows.

ANSWER: A

QUESTION NO: 9

A customer is planning to use the JetMirror functionality on their Hitachi NAS Platform.

Which two are required from the customer to plan the implementation? (Choose two.)

- A.** the size of the storage pools in use
- B.** the number of files used
- C.** the distance to the destination system
- D.** if systems are managed by a common SMU

ANSWER: C D

QUESTION NO: 10

The administrator of a production Hitachi NAS Platform connected to a Hitachi AMS2300 requires file level replication to another Hitachi NAS Platform. However, there is a concern over the large numbers of files and about the high change rate as the replication time window is small. What should be done to reduce the replication time?

- A.** Use Transfer Primary Access.
- B.** Use the changed directory list option.
- C.** Migrate the admin EVS to the node replicating the data.
- D.** Create an additional IP address on the source EVS.

ANSWER: B