

DUMPS ARENA

HCNA-UC (Unified Communication)

Huawei H11-811

Version Demo

Total Demo Questions: 15

Total Premium Questions: 235

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

Through the eSight version file management function, version files of IP phones can be updated and upgraded in batches.

- A. TRUE
- B. FALSE

ANSWER: A**QUESTION NO: 2**

Which of the following statements are CORRECT about data backup and restore on the IP PBX? (Multiple Choice)

- A. Data must be saved before each data backup.
- B. Data must be saved and then restart the IP PBX after importing the data.bin file during each data restore.
- C. Data does not need to be saved during data backup and restore.
- D. TFTP tool must be used to transmit the data.bin file.

ANSWER: A D**QUESTION NO: 3**

When configuring the U1960, which of the following boards do you need to add in the web management or Cli? (Multiple Choice)

- A. SCU
- B. MTU
- C. OSU
- D. ASI

ANSWER: B C D

QUESTION NO: 4

Which of the following statements are CORRECT about the number length specified by a prefix? (Multiple Choice)

- A. The minlen parameter indicates the minimum number length before number change.
- B. The minlen parameter indicates the minimum number length after number change.
- C. The maxlen parameter indicates the maximum number length before number change.
- D. The maxlen parameter indicates the maximum number length for the numbers after number change.

ANSWER: B D

QUESTION NO: 5

In the H.323 protocol suite, which protocol is responsible for call control?

- A. H.225
- B. H.235
- C. H.245
- D. H.450

ANSWER: A

QUESTION NO: 6

The U1900 main control board provides the following functions() (Multiple Choice)

- A. Generating original CDRs
- B. Processing and converting protocols such as SIP and H.248
- C. Voice codec standards such as G.711 and G.723
- D. TDM switching

ANSWER: A B D

QUESTION NO: 7

When adding new POTS users under a IAD, which type of number should be configured in the U1900?

- A. SIP
- B. POTS
- C. H.248
- D. BICC

ANSWER: A

QUESTION NO: 8

Assuming that user A has enabled password-based local call restriction, the call restriction prefix is 369, and the outgoing prefix is 0. Which of the following statements are

CORRECT? (Multiple Choice)

- A. User A dials the number of intra-office user B. The call is connected.
- B. User A dials 369, SSSSSS, 0, and outer-office user C's number. The call is connected.
- C. User A can use this password on multiple phones.
- D. User B who is enabled with local call restriction knows this password can also place an outgoing call.

ANSWER: A B

QUESTION NO: 9

The eSpace IPT solution architecture consists of several layers including terminal access, call control, and service application layers. Which of the following components belongs to the call control layer?

- A. IAD1224
- B. U1960
- C. eSpace 7910
- D. eSpace 8950

ANSWER: B

QUESTION NO: 10

Which of the following statements is CORRECT about the mode for querying the IP address of an IAD?

- A. Dial *125 on the phone connected to the IAD. Then, the voice announcement plays the IP address.
- B. Dial *128 on the phone connected to the IAD. Then, the voice announcement plays the IP address.
- C. Log in to the IAD through the serial port and run the display ipaddress command to view the IP address of the device.
- D. None of the above

ANSWER: C**QUESTION NO: 11**

IP phones can obtain IP addresses through the DHCP server to access the IP network.

- A. TRUE
- B. FALSE

ANSWER: A**QUESTION NO: 12**

Which of the following statements is CORRECT about the VU service of U1900?

- A. Only the script provided by the system can be used for configuring the automatic switchboard.
- B. The script for the automatic switchboard can be edited.
- C. Greetings of the conferences through individual dialing-in cannot be customized.
- D. A voice channel can store multiple voice files.

ANSWER: B**QUESTION NO: 13**

Which of the following statements are CORRECT in the CDR and billing scenario?

(Multiple Choice)

- A. CDR data needs to be finally imported into the CDRServer database.
- B. Users can query CDR data on U1900 web pages.
- C. In the CDR integration network, a third-party billing system functions as the FTP client.
- D. A single CDRServer can concurrently store and process CDR data from multiple IP PBXs.

ANSWER: C D

QUESTION NO: 14

Which of the following statements is INCORRECT about the mode for obtaining the IAD IP address?

- A. Set a static IP address for the IAD.
- B. Dynamically obtain the IP address through DHCP.
- C. Allow eSight to deliver the IAD IP address.
- D. Obtain the IP address through PPPoE.

ANSWER: C

QUESTION NO: 15

Which of the following statements are CORRECT? (Multiple Choice)

- A. The AT0 trunk is often used to implement DDI features.
- B. The SS7 trunk can be an ISUP trunk or a TUP trunk.
- C. The PRA can be configured at the user side or at the network side.
- D. SIP is a transport-layer control (signaling) protocol.

ANSWER: A B C