

DUMPS ARENA

Developing Applications for Cisco Webex and Webex Devices (DEVWBX)

Cisco 300-920

Version Demo

Total Demo Questions: 10

Total Premium Questions: 60

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

Topic Break Down

Topic	No. of Questions
Topic 1, Webex API Foundation	13
Topic 2, Meetings	13
Topic 3, Devices	12
Topic 4, Messaging	8
Topic 5, Embedding Webex	9
Topic 6, Administration and Compliance	5
Total	60

QUESTION NO: 1 - (DRAG DROP)

DRAG DROP

Drag and drop the expressions to create a Webex Teams widget that uses Guest Issuer to enable customers to chat and meet with agents. Not all options are used.

Select and Place:

```

<script>
$(document).ready(function () {
  $("#btn").click(function () {
    var widgetEL = document.getElementById('supportChart');
    $.ajax({
      url: '/api/getSession',
      type: 'POST',
      contentType: 'application/json',
      data: JSON.stringify({
        name: $("#name").val(),
        email: $("#email").val()
      })
    })
  }).done(function (session) {
    ciscospark.widget(widgetEl).spaceWidget({
      guestToken: ,
      destinationId: ,
      destinationType: ,
      activities: {"files": false, "meet": true, "message": true, "people": false},
      initialActivity: ,
      secondaryActivitiesFullWidth: false
    });
  })
})
</script>

```

```

app.post('/api/getSession', function(req, res) {
  res.status(200).send({
    agent: 'johndoe@example.com',
    token: jwt.sign({
      "sub": "${req.body.email}",
      "name": "${req.body.name}",
      "iss": "${issuer}"
    }, Buffer.from("${secret}", 'base64'), {})
  });
})

```

"userid"

"message"

session.token

Direct

session.agent

guest

ANSWER:

```

<script>
$(document).ready(function () {
  $("#btn").click(function () {
    var widgetEL = document.getElementById("supportChart");
    $.ajax({
      url: '/api/getSession',
      type: 'POST',
      contentType: 'application/json',
      data: JSON.stringify({
        name: $("#name").val(),
        email: $("#email").val()
      })
    }).done(function (session) {
      ciscospark.widget(widgetEL).spaceWidget({
        guestToken: guest
        destinationId: "userid"
        destinationType: session.token
        activities: {"files": false, "meet": true, "message": true, "people": false},
        initialActivity: session.agent
        secondaryActivitiesFullWidth: false
      });
    })
  })
})
</script>

```

```

"userid"
"message"
session.token
Direct
session.agent
guest

```

```

app.post('/api/getSession', function(req, res) {
  res.status(200).send({
    agent: 'johndoe@example.com',
    token: jwt.sign({
      "sub": "${req.body.email}",
      "name": "${req.body.name}",
      "iss": "${issuer}"
    }, Buffer.from("${secret}", 'base64'), {})
  });
})

```

Explanation:

QUESTION NO: 2

```
const Webex = require('webex');  
  
const webex = Webex.init({  
  credentials: {  
    access_token: 'A_VALID_ACCESS_TOKEN'  
  }  
});
```

Refer to the exhibit. When using the Webex Browser SDK to create calls and share screens, which two statements are valid given a 'webex' object such as displayed in the exhibit? (Choose two.)

- A. After a meeting is joined, it cannot be left programmatically until the host ends the meeting.
- B. The webex meetings.register() function must be invoked before attempting to join any meeting.
- C. The joinMeeting() function throws an error of type 'media stopped' if a media stream is stopped.
- D. Given a Webex meeting number the webex meetings join() function can be used to join the meeting.
- E. The mediaSettings for a joined meeting accepts boolean attributes to send and receive audio, video, and screen share.

ANSWER: A B

Explanation:

Reference: <https://developer.webex.com/docs/sdks/browser>

QUESTION NO: 3

```
1  const WebExClient = require('webex-api-client');
2  const securityContext = {
3    webExID: 'Test User',
4    password: 'pass123',
5    siteName: 'hello-world'
6  };
7
8  const requestBuilder = new WebExClient.Builder
9  (securityContext, 'https://hello-world.webex.com/WBXService/XMLService');
10
11 const createMeeting =
12   requestBuilder
13   .metaData({
14     confName: 'Sample Meeting',
15     meetingType: 1,
16   })
17   .participants({
18     attendees: [
19       {
20         name: 'Jane Doe',
21         email: 'jdoe@gmail.com'
22       }
23     ]
24   })
25   .schedule({
26     startDate: new Date(),
27     _____,
28     _____
29   })
30   .setService('CreateMeeting')
31   .build();
32
33 createMeeting
34   .exec()
35   .then((resp) => console.log('success'));
36
37
```

Refer to the exhibit. Which code for blank lines 26, 27, and 28 gives invitees 900 seconds before the scheduled time to join the meeting, sets the meeting to last for 30 minutes, and sets the meeting timezone to Pacific US?

A.

```
26  openMeeting: 900
27  stopTime: 30,
28  timeZone: 4
```

B.

```
26  openTime: 900
27  duration: 30,
28  timeZoneID: 4
```

- C.

```
26 joinTime: 900
27 meetingLength: 30,
28 timezone: 5
```
- D.

```
26 joinTime: 900
27 endTime: 30,
28 timezoneID: pt_us
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

ANSWER: B

Explanation:

Reference: <https://github.com/cisco-ie/webex-api-client>

QUESTION NO: 4

A company wants to adopt Webex Teams as a messaging platform and use REST APIs to automate the creation of teams and rooms. Which sequence of REST API requests is needed to create and populate a new Webex team and create a populated Webex room for the team?

- A. POST /teams, POST /memberships, POST /rooms
- B. POST /teams, POST /people, POST /rooms
- C. POST /teams, POST /team/memberships, POST /rooms
- D. POST /teams, POST /team/memberships, POST /rooms, POST /memberships

ANSWER: B

Explanation:

Reference: <https://developer.webex.com/docs/api/basics>

QUESTION NO: 5

Which two tasks should use a Webex bot instead of a Webex integration? (Choose two.)

- A. Ask a question in natural language to obtain the current price of a stock.
- B. Translate a word or phrase from Italian to English.
- C. Notify all users who send a 1:1 message that the user is currently out of the office.
- D. Automatically delete a message that was sent with spelling or grammatical errors.
- E. Archive all the messages in a group space.

ANSWER: A B

Explanation:

Reference: <https://developer.webex.com/docs/bots>

QUESTION NO: 6

```
{
  "items":
  {
    "id": "Y21zY29zcGFyazovL3VzL1LWT4Y2UtMTEzZjZjZmMxNGJl",
    "title": "DevNet Dev Support Questions",
    "lastActivity" : "2019-12-13T21:32:11.424Z",
    "created": "2016-01-22T19:07:24.785Z",
    ...
  },
  {
    "id": "Y21zY29zcGFyazovL3VzWU1LWT0ZjZjZmJmMjI3Y2ZmYWYz",
    "title": "DevNet Program Questions",
    "lastActivity" : "2019-12-13T16:53:14.920Z",
    "created": "2016-02-24T18:52:35.013Z",
    ...
  }
}
```

Refer to the exhibit. Which Webex Teams REST API request has generated the response body in the exhibit?

- A. GET/v1/rooms?sortBy=lastactivity
- B. GET/v1/rooms?sortBy=created
- C. GET/v1/rooms?max=1
- D. GET/v1/spaces?orderBy=lastActivity

ANSWER: C**Explanation:**Reference: <https://developer.webex.com/docs/api/v1/rooms/list-rooms>**QUESTION NO: 7**

With CE 9.8 and above, which two statements are correct when an application is sending and receiving data over a connection established with an xAPI interface? (Choose two.)

- A. All Serial, SSH, and WebSockets can be used to send and receive data.
- B. HttpClient can be used to send requests but not receive responses.
- C. HttpFeedback is the only option to receive data.
- D. The HttpClient command can be used to send requests and read responses over HTTP.
- E. WebSockets is the only option to send and receive data.

ANSWER: B D**Explanation:**Reference: <https://www.cisco.com/c/dam/en/us/td/docs/telepresence/endpoint/ce98/sx-mx-dx-room-kit-boards-customization-guide-ce98.pdf>**QUESTION NO: 8**

Which two filters are valid for limiting a webhook? (Choose two.)

- A. roomId=
- B. personId!=
- C. spaceId=
- D. personId=\$spaceId=
- E. personId=\$roomId=

ANSWER: A B**Explanation:**Reference: <https://developer.webex.com/docs/api/guides/webhooks>

QUESTION NO: 9 - (DRAG DROP)

DRAG DROP

Create a Membership

Add someone to a room by Person ID or email address; optionally making them a moderator.

POST /v1/memberships

Body Parameters

roomId
string **Required**
The room ID.

personID
string
The person ID.

personEmail
string
The email address of the person

isModerator
boolean
Whether or not the participant is a room moderator

Refer to the exhibit. Drag and drop the code on the snippet to add the user with email "alice@example.com" as moderator of the space with the identifier "987654321".

Select and Place:

```
curl -s -X [ ] "https://api.ciscospark.com/v1/[ ]" \
-H "Authorization: Bearer MDMyZTM1YTA_Pf84_1eb65fdf-ad72cae0e10f" \
-H "Content-Type: application/json" \
-data-raw '{" [ ] "987654321" [ ] "alice@example.com" "isModerator" [ ] "}'
```

[personEmail] [true] [POST] [memberships] [roomId]

ANSWER:

```
curl -s -X [ POST ] "https://api.ciscospark.com/v1/[ memberships ]" \
-H "Authorization: Bearer MDMyZTM1YTA_Pf84_1eb65fdf-ad72cae0e10f" \
-H "Content-Type: application/json" \
-data-raw '{" [ roomId ] "987654321" [ personEmail ] "alice@example.com" "isModerator" [ true ] "}'
```

[personEmail] [true] [POST] [memberships] [roomId]

Explanation:

Reference: <https://developer.webex.com/docs/api/v1/memberships/create-a-membership>

QUESTION NO: 10

What happens if a meeting is in progress when a DelMeeting request is sent in the Webex Meetings XML API?

- A. The meeting host is notified and prompted to allow the meeting to be deleted.
- B. The DelMeeting request drops all call-in users and deletes the meeting.
- C. The DelMeeting request waits until the meeting is completed and then deletes the meeting.
- D. The DelMeeting request results in an error.

ANSWER: A**Explanation:**

Reference: <https://pdfslide.net/documents/webex-we.html> (p.216)