

DUMPS ARENA

Specialist - Implementation Engineer SC Series Exam

EMC DES-1721

Version Demo

Total Demo Questions: 10

Total Premium Questions: 147

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

How many SC420 enclosures can be supported by the SC7020 controller?

- A. 4
- B. 8
- C. 6
- D. 12

ANSWER: B**QUESTION NO: 2**

You want to create a notification setting to help monitor how full the volumes are on an SC9000 system. In Dell Storage Manager (DSM), where would a schedule to only trigger these alerts during business hours be set up?

- A. "Edit Automated Report Settings"
- B. "Edit Data Collector Settings"
- C. "Threshold Alerts" Definition
- D. "Storage Center Summary" Report

ANSWER: B**QUESTION NO: 3**

Which zones accurately describe the zoning requirement for replication connectivity to be established when the source array is in Legacy Port Mode and the target array is in Virtual

Port Mode?

- A. Zone 1 = All Source Virtual Port WWNs + All Remote Physical Port WWNs
Zone 2 = All Source Physical Port WWNs + All Remote Virtual Port WWNs
- B. Zone 1 = All Physical WWNs from both arrays
Zone 2 = All Virtual WWNs from both arrays
- C. Zone 1 = All Source WWNs + All Remote Virtual Port WWNs
Zone 2 = All Source WWNs + All Remote Physical Port WWNs

D. Zone 1 = All Source Virtual Port WWNs + All Remote Port WWNs
Zone 2 = All Source Physical Port WWNs + All Remote Port WWNs

ANSWER: B

QUESTION NO: 4

An administrator wants to configure an SC Series array to use Virtual Port Mode. What is a requirement to accomplish this task?

- A. I/O Controller cards must use a single-ID firmware version
- B. Activation license must be installed
- C. NPIV must be disabled on Fibre Channel switches
- D. Fibre Channel switches must use an arbitrated loop topology

ANSWER: D

Explanation:

:

Reference <https://www.dell.com/support/manuals/lt/en/ltbsdt1/dell-compellentssc4020/sc4020om-v8/requirements-for-virtual-port-mode?guid=guid-90fdb7bf-141b-4218b3e5-2acb34acf90d&lang=en-us>

QUESTION NO: 5

You are implementing a front-end connection in Legacy Port Mode on an SC4020 in a SAN with two iSCSI switches. What is the minimum number of port(s), per switch, that can be used by each controller?

- A. One port on each Ethernet switch
- B. Two ports on each Ethernet switch
- C. Four ports on each Ethernet switch
- D. Eight ports on each Ethernet switch

ANSWER: C

QUESTION NO: 6

You just finished racking a SC7020 array. After powering it on, you notice there is no indicator LED on the front or back of the array, but the fans are spinning.

What could be the cause?

- A. 220VAC is being used. The system is preventing a fire hazard
- B. Controllers are misplaced. Swap the position of the controllers
- C. 110VAC is being used on the power mains
- D. The SC is overheated; let it cool down

ANSWER: C**QUESTION NO: 7 - (DRAG DROP)**

DRAG DROP

You have just deployed an SC Series array in Virtual Port Mode. What is the correct sequence of steps to perform an array port failover test?

Select & Place:

Confirm I/O is being received on the selected volume in the DSM GUI	STEP 1
Physically disconnect the port that matches the identified controller port	STEP 2
Send I/O from the host to an existing single path volume on the array	STEP 3
Confirm I/O is still being received on the selected volume in the DSM GUI	STEP 4
Confirm the WWN for the controller port intended to failover in the DSM GUI	STEP 5

ANSWER:

Confirm I/O is being received on the selected volume in the DSM GUI

Physically disconnect the port that matches the identified controller port

Send I/O from the host to an existing single path volume on the array

Confirm I/O is still being received on the selected volume in the DSM GUI

Confirm the WWN for the controller port intended to failover in the DSM GUI

Confirm I/O is being received on the selected volume in the DSM GUI

Physically disconnect the port that matches the identified controller port

Send I/O from the host to an existing single path volume on the array

Confirm the WWN for the controller port intended to failover in the DSM GUI

Confirm I/O is still being received on the selected volume in the DSM GUI

QUESTION NO: 8

What is a minimum recommended redundancy to support Controller port level failover?

- A. Two Fault Domains with two ports each
- B. Four Fault Domains with one port each
- C. Two Fault Domains with one port each
- D. One Fault Domain with four ports

ANSWER: C**QUESTION NO: 9**

What three core features are part of the protection bundle?

- A. Live Volume, Remote Instant Replay, Replay Manager
- B. Data Progression, Remote Instant Replay, Replay Manager
- C. Live Volume, Data Progression, Replay Manager
- D. Live Volume, Remote Instant Replay, FastTrack

ANSWER: A

QUESTION NO: 10

Why would the Key Management Server (KMS) Settings page appear during installation?

- A. Page appears only if SED drives are present
- B. Page only appears if an external KMS is defined during setup and configuration
- C. Page is standard and always appears as part of the installation and configuration
- D. Page only appears if a security certificate is not generated

ANSWER: A