

DUMPS ARENA

Oracle Database Administration II

Oracle 1z0-083

Version Demo

Total Demo Questions: 10

Total Premium Questions: 152

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

Which three are true about using Database Resource Manager in an Oracle multitenant environment? (Choose three.)

- A. A PDB-level resource plan can limit session PGA memory.
- B. A CDB-level resource plan can limit PDB CPU utilization.
- C. A CDB-level resource plan can limit session CPU utilization.
- D. PDB-level resource plans can limit uncommitted UNDO per consumer group.
- E. A CDB-level resource plan can limit PDB UNDO use.
- F. A CDB-level resource plan is mandatory when using PDB-level resource plans.

ANSWER: C E F**QUESTION NO: 2**

A schema owner truncated a table in error and must recover the data.

Which Oracle Flashback feature could be used to recover the data?

- A. FLASHBACK TRANSACTION
- B. FLASHBACK VERSION QUERY
- C. FLASHBACK DATA ARCHIVE
- D. FLASHBACK TABLE
- E. FLASHBACK DATABASE

ANSWER: B

Explanation:

Reference: https://docs.oracle.com/cd/B12037_01/appdev.101/b10795/adfns_fl.htm

QUESTION NO: 3

Application PDBs, SALES_APP1 and SALES_APP2, must be created and they must access common tables of the SALES_APP application.

Examine these steps:

1. Install the SALES_APP application, including the common tables, in the application root.
2. Install the SALES_APP application in the application root and the common tables in both the CDB root and the application root.
3. Create an application seed.
4. Install the SALES_APP application in the application seed.
5. Create the SALES_APP1 and SALES_APP2 application PDBs.
6. Sync the SALES_APP1 and SALES_APP2 application PDBs with the application root.
7. Sync the SALES_APP1 and SALES_APP2 application PDBs with the application seed.
8. Sync the application seed with the application root.

Which are the minimum required steps in the correct sequence?

- A. 3, 4, 1, 6, 8
- B. 2, 5, 6
- C. 1, 5, 6
- D. 1, 3, 5, 6, 7
- E. 1, 3, 5, 7

ANSWER: C

QUESTION NO: 4

Examine this configuration:

1. CDB1 is an Oracle Database 12c Release 2 database containing pluggable databases PDB\$SEED, PDB1, and PDB2.
2. PDB\$SEED is open READ ONLY 3. PDB1 is open READ WRITE
4. PDB2 is MOUNTED.
5. ORACLE_HOME is /u01/app/oracle/product/18.1.0/dbhome_1.

You execute these commands before upgrading the database to the current release:

```
$ . oraenv
ORACLE_SID = [cdb1] ? cdb1
The Oracle base remains unchanged with value /u01/app/oracle

$ $ORACLE_HOME/jdk/bin/java -jar preupgrade.jar TERMINAL TEXT
```

For which databases will fixup scripts be created?

- A. CDB1, PDB\$SEED, PDB1, and PDB2
- B. PDB\$SEED, PDB1, and PDB2 only
- C. CDB1 and PDB\$SEED only
- D. CDB1, PDB1, and PDB2 only
- E. CDB1, PDB\$SEED, and PDB1 only

ANSWER: E

QUESTION NO: 5

A database is configured in ARCHIVELOG mode.

A full RMAN backup exists but no control file backup to trace has been taken.

A media failure has occurred.

In which two scenarios is incomplete recovery required? (Choose two.)

- A. after losing a SYSAUX tablespace data file
- B. after losing all members of an INACTIVE online redo log group
- C. after losing all members of the CURRENT online redo log group
- D. after losing all copies of the control file
- E. after losing an UNDO tablespace that is in use

ANSWER: B D

QUESTION NO: 6

Which operating system group is NOT needed to perform an Oracle Database installation?

- A. OSASM
- B. OSKMDBA
- C. OSDBA
- D. OSOPER
- E. OSRACDBA

ANSWER: E**Explanation:**Reference: https://docs.oracle.com/database/121/LADBI/usr_grps.htm#LADBI2820**QUESTION NO: 7**

Which three are true about creating container databases (CDBs) and pluggable databases (PDBs) in Oracle 19c and later releases? (Choose three.)

- A. A PDB snapshot can be a sparse copy of a source PDB.
- B. A PDB snapshot depends on an existing storage snapshot of the source PDB.
- C. A CDB can be duplicated using Recovery Manager (RMAN) with no configuration required before starting the duplication.
- D. A CDB can be duplicated using the Database Configuration Assistant (DBCA) in silent mode with no configuration required before starting the duplication.
- E. A PDB snapshot can be a full copy of a source PDB.
- F. A snapshot copy PDB can be a full copy of a source PDB.
- G. A snapshot copy PDB does not depend on an existing storage snapshot of the source PDB.

ANSWER: A B F**Explanation:**Reference: <https://docs.oracle.com/en/database/oracle/oracle-database/19/multi/cloning-a-pdb.html#GUID-05702CEB-A43C-452C-8081-4CA68DDA8007>**QUESTION NO: 8**

Which two are true about an RPM-based Oracle Database installation? (Choose two.)

- A. It uses a service configuration script to create a single-instance database as part of the installation.
- B. From Oracle Database 18c, a single RPM can be used to install only Oracle Database Server for a single instance.
- C. It performs a software-only Oracle Database installation.
- D. It includes the Oracle Preinstallation RPM.
- E. It requires an Unbreakable Linux Network (ULN) subscription.

ANSWER: D E**Explanation:**

Reference: <https://docs.oracle.com/en/database/oracle/oracle-database/18/ladbi/running-rpm-packages-to-install-oracle-database.html#GUID-BB7C11E3-D385-4A2F-9EAF-75F4F0AACF02>

QUESTION NO: 9

Which two are true about RMAN encryption? (Choose two.)

- A. RMAN encryption keys are stored in a database keystore.
- B. RMAN can encrypt the Oracle Database password file.
- C. Dual-mode encrypted backups can be restored only if both the password and the keystore used for encryption are available.
- D. The SET ENCRYPTION command overrides encryption settings specified by the CONFIGURE ENCRYPTION command.
- E. Password encryption can be persistently configured using the CONFIGURE ENCRYPTION command.

ANSWER: C D**Explanation:**

Reference: <https://docs.oracle.com/database/121/BRADV/rcmconfa.htm#BRADV89476>

QUESTION NO: 10

Examine these queries and their output:

```
SQL> select pdb_name, name, pdb_restore_point, clean_pdb_restore_point
  2 from v$restore_point natural join dba_pdbs;
```

PDB_NAME	NAME	PDB_RESTORE_POINT	CLEAN_PDB_RESTORE_POINT
PDB1	R1	YES	NO

```
SQL> select property_name, property_value
  2 from database_properties where property_name like '%UNDO%';
```

PROPERTY_NAME	PROPERTY_VALUE
LOCAL_UNDO_ENABLED	FALSE

An online RMAN backup of the CDB was taken an hour before Restore Point R1 was created.

You want to recover PDB1 to Restore Point R1.

How do you achieve this?

- A.** Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using RMAN while connected to PDB1.
- B.** Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using SQL while connected to PDB1.
- C.** Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using SQL while connected to CDB\$ROOT.
- D.** Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using RMAN while connected to CDB\$ROOT.
- E.** This cannot be done due to the lack of a clean restore point.

ANSWER: B