

DUMPS ARENA

Delta - Building HPE Hybrid IT Solutions

HP HPE0-V15

Version Demo

Total Demo Questions: 10

Total Premium Questions: 80

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

A customer requests a quote for an HPE storage solution that meets these requirements

- fully redundant dual-controller storage array with no single points of failure
- 1 Gb or 10 Gb iSCSI connectivity
- at least four host-facing iSCSI ports
- capable of expanding usable capacity in small increments of one-to-two disks

Which HPE storage solution should be proposed?

- A. D3000
- B. MSA 1050
- C. Nimble AF20Q
- D. Nimble HF20

ANSWER: B**QUESTION NO: 2 - (DRAG DROP)**

Match the customer requirement to the appropriate HPE storage solution.

HPE Solution

HPE 3PAR Storage

HPE MSA Storage

HPE Nimble Storage

Requirement

Converged block, file, and object

Triple-Parity RAID

Volume Tier Affinity

ANSWER:

HPE Solution

HPE 3PAR Storage

HPE MSA Storage

HPE Nimble Storage

HPE 3PAR Storage

HPE Nimble Storage

HPE MSA Storage

Requirement

Converged block, file, and object

Triple-Parity RAID

Volume Tier Affinity

Explanation:

HPE Solution

HPE 3PAR Storage

HPE MSA Storage

HPE Nimble Storage

HPE 3PAR Storage

HPE Nimble Storage

HPE MSA Storage

Requirement

Converged block, file, and object

Triple-Parity RAID

Volume Tier Affinity

Reference:

<https://h20195.www2.hpe.com/v2/GetPDF.aspx/4AA5-6078ENW.pdf>

<https://assets.ext.hpe.com/is/content/hpedam/a50002410enw>

QUESTION NO: 3

A customer needs to integrate a new digital video surveillance solution into their existing environment and available network ports. The solution needs to include redundant hypervisor servers and a redundant SAN with a shared Fibre Channel attached storage array.

You plan to propose the following configuration:

What must be added to the configuration to provide a complete solution? (Choose two.)

- A. 2 HPE 10/25 Gb 2-port 622FLR-SFP28 CNA
- B. 2 HPE FlexFabric 5710 switches
- C. 2 Aruba 8320 switches
- D. 2 HPE SN3000B switches
- E. 2 HPE StoreFabric SN1200E 16 Gb Dual Port FC HBAs

ANSWER: D E

QUESTION NO: 4

Why is SNMPv2c considered to be insecure?

- A. SNMPv2c agents only accept GET requests which match their read-only community string
- B. SNMPv2c community strings are transmitted in clear text
- C. SNMPv2c only allows the signing of the message payload
- D. SNMPv2c agents only encrypt WRITE messages.

ANSWER: B

QUESTION NO: 5

A system administrator is performing the BIOS/Platform configuration of a DL380 Gen10 servers You notice the amber health LED.

The health status of which solution components can be verified with embedded UEFI Diagnostics? {Select two.}

- A. Primera node
- B. iLONAND
- C. FC HBA
- D. Processor
- E. Power Supplies

ANSWER: B D

QUESTION NO: 6 - (HOTSPOT)

A solution Integrator is installing new equipment to the rack Click the recommended location area for R3000 Gen5 UPS.




ANSWER:



Explanation:

QUESTION NO: 7

Refer to the exhibit.



You are configuring a pair of HPE 5945 switches into an IRF stack. You have cabled the switches as depicted in the exhibit. Into which IRF Ports should you place each switch interface?

A)

```
IRF Port1/1 -interface Ten-GigabitEthernet 1/0/31 -interface Ten-GigabitEthernet 2/0/32
IRF Port2/1 -interface Ten-GigabitEthernet 1/0/31 -interface Ten-GigabitEthernet 2/0/32
```

B)

```
IRF Port1/1 -interface Ten-GigabitEthernet 2/0/31 -interface Ten-GigabitEthernet 2/0/32
IRF Port2/1 -interface Ten-GigabitEthernet 1/0/31 -interface Ten-GigabitEthernet 1/0/32
```

C)

```
IRF Port1/1 -interface Ten-GigabitEthernet 1/0/32 -interface Ten-GigabitEthernet 2/0/31
IRF Port2/1 -interface Ten-GigabitEthernet 1/0/31 -interface Ten-GigabitEthernet 2/0/32
```

D)

```
IRF Port1/1 -interface Ten-GigabitEthernet 1/0/31 -interface Ten-GigabitEthernet 1/0/32
IRF Port2/1 -interface Ten-GigabitEthernet 2/0/31 -interface Ten-GigabitEthernet 2/0/32
```

A. Option A

B. Option B

C. Option C

D. Option D

ANSWER: A**QUESTION NO: 8**

An administrator deployed a new FlexFabric switch into the environment and wants to collect baseline information from the switch. The administrator wants to be able to use this in case there is any question from support should the administrator open a case.

Which command can the administrator use to collect support information from the switch?

A. support save

B. show switch info

C. display diagnostic-information

D. show tech all

ANSWER: C**Explanation:**

<https://support.hpe.com/hpsc/public/docDisplay?docId=c04406895>

QUESTION NO: 9

A customer needs to deploy an application on a newly-installed HPE ProLiant server, but they report that the server is not online. They call you for remote support. The IP address on the production network cannot be reached. You are evaluating the probable root causes of this issue.

According to the troubleshooting methodology, what are next two steps? (Select two)

- A. Remote console into the ToR switch to check the server's port configuration.
- B. Log in to iLO to see if the server hardware and NIC are online and configured correctly.
- C. Use OneView to see if the server firmware is up-to-date
- D. Run insight Diagnostics on the Server
- E. Use Microsoft Remote Desktop or VNC to check the server's NIC and IP address configuration

ANSWER: B D**QUESTION NO: 10**

For which virtualization management products does HPE OneView offer integration plug-ins? (Select two.)

- A. Nutanix Prism infrastructure Manager
- B. Red Hat Enterprise Virtualization Manager
- C. Microsoft System Center
- D. VMware vCenter
- E. Citrix XenCenter

ANSWER: C D