

DUMPS ARENA

IBM Spectrum Protect V8.1 Administration

IBM C9060-528

Version Demo

Total Demo Questions: 10

Total Premium Questions: 128

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

How does an IBM Spectrum Protect administrator ensure that only the IBM Spectrum Protect server will start scheduled sessions with clients?

- A. SESSIONINITIATION PROMPTED
- B. SESSIONINITIATION CLIENTORSERVER
- C. SESSIONINITIATION SERVERONLY
- D. SESSIONINITIATION POLLING

ANSWER: C**Explanation:**

SESSIONINITiation controls whether the server or the client initiates sessions. The default is that the client initiates sessions.

SERVEROnly specifies that the server does not accept client requests for sessions.

References: IBM Spectrum Protect for Windows Version 8.1.0, Administrator's Reference, p 1090

QUESTION NO: 2

Which two capabilities are provided with the IBM Spectrum Protect incremental forever backup method? (Choose two.)

- A. increase the total number of bytes sent to the protect server
- B. reduce the time needed to perform a restore of a system
- C. reduce the total storage used to save backups of the system
- D. provide the ability to use LAN-Free backups
- E. perform a point-in-time restore

ANSWER: B C**Explanation:**

C: The incremental forever backup solution provides these advantages:

B: In addition, the restore process is optimized, as only the latest versions of blocks that belong to a restored backup are restored. Since the same area on the production disk is recovered only one time, the same block is not written to multiple times. As a result of these advantages, incremental forever is the preferred backup strategy.

References: https://www.ibm.com/support/knowledgecenter/en/SSERB6_8.1.0/ve.hv/c_ve_hv_bup_incrforever.html

QUESTION NO: 3

In addition to Add Alert and Delete Alert, which two actions can be configured in the Alerts tab? (Choose two.)

- A. Add Category
- B. Import Alert
- C. Change Category
- D. Configure Notification
- E. Export Alert

ANSWER: D E**Explanation:**

References:

QUESTION NO: 4

Which backup-archive client host operating system requires the use of a dsm.sys file?

- A. UNIX/Linux
- B. Microsoft Windows workstation system
- C. any server in a Microsoft Windows cluster
- D. Microsoft Windows server 2008

ANSWER: A**Explanation:**

Configure the IBM Spectrum Protect client

After installing the backup-archive client, you must configure it before performing any operations.

The following applies to AIX, Linux, Solaris, and Mac OS X.

If you are upgrading the backup-archive client, it is unnecessary to reconfigure the scheduler, web client, or other configuration settings. If the dsm.opt and dsm.sys files used by the previous client installation are available in the default installation directory or the directory or file pointed to by the DSM_CONFIG and DSM_DIR environment variables, the client accesses these files for configuration information.

References: https://www.ibm.com/support/knowledgecenter/en/SSEQVQ_8.1.0/client/c_cfg.html

QUESTION NO: 5

What is the purpose of the UPDATE NODE BKREPLRULEDEFAULT= server command?

- A. update the node settings by changing the default replication rule for Space Management data
- B. update the node settings by changing both the default replication rule for backing up and archiving data
- C. update the node settings by changing the default replication rule for archiving data
- D. update the node settings by changing the default replication rule for backing up data

ANSWER: D

Explanation:

BKREPLRuledefault specifies the replication rule for backup data.

ARREPLRuledefault specifies the replication rule for archive data.

SPREPLRuledefault specifies the replication rule for space-managed data.

References: IBM Spectrum Protect for Windows Version 8.1.0, Administrator's Reference, p 1091

QUESTION NO: 6

What are three purposes of IBM Spectrum Protect for Mail for Exchange? (Choose three.)

- A. Provides full recovery of Microsoft Exchange email only by Search capabilities and by using Microsoft backup APIs
- B. Uses custom APIs provided by vendor to perform offline and online backups of Microsoft Exchange clients
- C. By using Microsoft backup API, it provides the possibility to back up Exchange Server only when they are in DAG configuration
- D. Uses Microsoft backup APIs to create a copy of Exchange server storage group databases and the associated transaction logs
- E. Uses APIs provided by vendors to perform online hot backups and improve restores without shutting down the email application
- F. Provides item-level recovery of Microsoft Exchange email object by Search capabilities

ANSWER: D E F

QUESTION NO: 7

On an IBM Spectrum Protect Linux server, a data migration to tape has failed with a device error.

Which output should be reviewed to get detailed error information?

- A. actlog
- B. /var/log/messages
- C. errpt

D. dsmerr

ANSWER: A

Explanation:

References:

QUESTION NO: 8

What is true regarding an administrator who has been granted restricted storage authority?

- A. This administrator can delete storage specific storage pools.
- B. This administrator can control specific storage resources.
- C. This administrator can control all storage resources.
- D. This administrator can only add storage resources to all storage.

ANSWER: A

Explanation:

Restricted Storage: Manage server storage, but limited to specific storage pools.

References:

https://www.ibm.com/support/knowledgecenter/en/SSGSG7_6.3.4/com.ibm.itsm.srv.doc/r_mgclinod_adminauthclass.html

QUESTION NO: 9

What are three required settings to configure server-to-server communication? (Choose three.)

- A. SET SERVERHLADDRESS
- B. SET LLAADDRESS
- C. SET SERVERNAME
- D. SET CONFIGMANAGER ON
- E. SET CROSSSERVER ON
- F. SET SERVERPASSWORD

ANSWER: A C F

Explanation:

Example: Cross-define two servers

Use cross definition to define SERVER_A and SERVER_B.

On SERVER_B, specify the server name, password, and high- and low-level addresses of SERVER_B. Specify that cross defining is allowed.

```
set servername server_b
```

```
set serverpassword mylife
```

```
set serverhladdress 9.115.20.80
```

```
set serverlladdress 1860
```

```
set crossdefine on
```

References: https://www.ibm.com/support/knowledgecenter/en/SSEQVQ_8.1.2/srv.reference/r_cmd_server_define.html

QUESTION NO: 10

Which three values can be adjusted with the Alerts Retention settings in the Operations Center? (Choose three.)

- A. Alert log pruning
- B. Closed alerts are retained
- C. Alerts stay active
- D. Alert log location
- E. Alerts stay inactive
- F. Active alerts changed to inactive

ANSWER: B C F**Explanation:**

B: Choose one of the following options to define when an alert in the closed state is deleted from the Tivoli Storage Manager server:

Delete the alert as soon as its state is changed to closed.

Delete the alert after it is in the closed state for a defined time interval.

F: From the Operations Center, you can change the alert state from active to inactive.