

DUMPS ARENA

Nokia IS-IS Routing Protocol

Nokia 4A0-112

Version Demo

Total Demo Questions: 8

Total Premium Questions: 45

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

Your HR department has spreadsheets with payroll information on a Windows Server 2003 file server to which only HR personnel have access. You have implemented IPSec policies on the server to ensure that data exchanged is more secure, by requiring IPSec for all connections to the server. All of your HR desktops are Windows XP Professional and Windows NT 4.0 Workstation SP5 clients. The Windows XP clients can access the files without problems, but the Windows NT 4.0 clients cannot. What can you do to resolve this issue without changing the security on the file server?

- A. Install Windows NT 4.0 SP6a on the Windows NT clients.
- B. Upgrade the Windows NT 4.0 Workstation clients to Windows XP Professional.
- C. Install the IPSec client on the Windows NT 4.0 Workstations.
- D. Enable NetBIOS over TCP/IP on the Windows Server 2003 machine.

ANSWER: B**QUESTION NO: 2**

You configure a Windows 2003 dial-up RAS gateway for a remote office in your corporate network. A dial-up ISDN connection is used to connect the remote office to the corporate LAN. In order to provide access for the remote users to the corporate LAN, what two configuration settings do you need to complete? (Choose all that apply.)

- A. Configure NAT on the ISDN interface.
- B. Configure a demand-dial interface on the ISDN interface.
- C. Configure a DHCP relay agent on the ISDN interface.
- D. Configure a default static route on the ISDN interface.

ANSWER: B D**QUESTION NO: 3**

You work as the network administrator at ABC.com. The ABC.com network has a domain named ABC.com. The servers at the ABC.com network run Windows Server 2003 and the workstations, Windows XP Professional.

The ABC.com network has a server named ABC-SR10 that runs Windows Server Update Services (WSUS). During synchronization you notice that you cannot connect to the Windows Update servers, however, you can access to other Web site not residing in the intranet.

What actions must you take to connect to the Windows Update servers?

- A. You must run the ipconfig/registerdns.

- B. You must configure the forwarders on ABC-SR10.
- C. You must set the authentication to the proxy server in the WSUS settings.
- D. You must run the `gpupdate /force` command on ABC-SR10.

ANSWER: C

QUESTION NO: 4

You work as the network administrator at ABC.com. The ABC.com network consists of a single Active Directory domain named ABC.com. The servers at the ABC.com network run Windows Server 2003 and the workstations, Windows XP Professional.

The ABC.com network has a DNS server named ABC-SR03 that does name resolution for host on the Internet. ABC.com users complain that they do not get the correct site when trying to access Web site known to them.

What actions must you take to stop this from happening without disrupting production?

- A. You should restart the DNS Server service.
- B. You should select the Secure cache against pollution setting.
- C. You should run the `ipconfig/flushdns` on ABC-SR03.
- D. You should run the `ipconfig/registerdns` on ABC-SR03.

ANSWER: B

QUESTION NO: 5

You work as the network administrator at ABC.com. The ABC.com network has a domain named ABC.com. The servers at the ABC.com network run Windows Server 2003 and the workstations, Windows XP Professional.

During the course of the day you have received instructions from the CIO to implement Windows Server Update Services (WSUS) on a server named ABC-SR10. However, ABC0SR10 has limited disk space so you must conserve disk space usage. You must also ensure that all updates are approved before they are applied.

What steps must you take after clearing the Automatically Approve Updates for Installation checkbox and opening the WSUS console? (Choose all that apply.)

- A. You should modify the Revisions to Updates setting to deselect the automatically approve all updates.
- B. You should set the demand-dial connection to Persistent.
- C. You should execute the `gpupdate` command on all client computers.
- D. You should modify the Advanced Synchronization Options dialog box to stop the locally stored updates.
- E. You should apply the Setup security.inf security template.

F. You should deselect the Automatically Approve Updates for Installation checkbox.

ANSWER: A D F

QUESTION NO: 6

You work as the network administrator at ABC.com. The ABC.com network has a domain named ABC.com. The servers at the ABC.com network run Windows Server 2003 and the workstations, Windows XP Professional Service Pack 2.

ABC.com makes use of a firewall between their intranet and the Internet. The firewall is configured to allow only HTTP traffic through. You have implemented a DNS server named ABC-SR04 with the default settings.

What actions must you take to make sure that ABC-SR04 can perform name resolution for Internet names?

- A. You should use port 110.
- B. You should use port 53.
- C. You should use port 80.
- D. You should use port 443.

ANSWER: B

QUESTION NO: 7

You work as the network administrator at ABC.com. The ABC.com network has of a domain named ABC.com. The servers at the ABC.com network run Windows Server 2003 and the workstations, Windows XP Professional.

The ABC.com network contains a server named ABC-SR20. ABC-SR20 contains an in-house application that runs as a service named NetApp1, which fails from time to time. During the course of the day you have received instructions from the CIO to implement the following process for NetApp1:

- The NetApp1 service should be restarted if it fails after running for at least a day.
- ABC-SR20 should be restart if the NetApp1 service fails unsuccessful the entire workday, the server should be rebooted.

What actions must you take to implement this plan? (Choose all that apply.)

- A. You need to enable the Master Key perfect forward secrecy (PFS).
- B. You need to set up the response to the first and second failure to restart NetApp1.
- C. You need to apply the Securews.inf security template.
- D. You need to set up the Reset fail count after value for NetApp1 to 1 day.
- E. You need to disable all services that are not required.

ANSWER: B D

QUESTION NO: 8

You work as the network administrator at ABC.com. The ABC.com network consists of a domain named ABC.com. The servers at the ABC.com network run Windows Server 2003 and the workstations run a mix of operating systems.

The ABC.com network has a multi-homed named ABC-SR24 that has the Routing and Remote Access Service (RRAS) installed. A new ABC.com security policy requires that ABC-SR24 be configured to only support connections from computers running Windows 95, Windows 98, Windows 2000 Professional, and Windows XP Professional.

What actions must you take to use a secure authentication method suitable for the operating system?

- A. You need to enable Kerberos V5.
- B. You need to enable NTLMv2.
- C. You need to enable MS-CHAP Version 1 and 2.
- D. You need to enable EAP-TLS.

ANSWER: C