

DUMPS ARENA

Service Provider Routing and Switching, Specialist (JNCIS-SP)

Juniper JN0-363

Version Demo

Total Demo Questions: 10

Total Premium Questions: 65

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

Exhibit

```
(edit)
user@router# set routing-options nonstop-routing
(edit)
user@router#
```

Referring to the exhibit, which two additional steps should you take to fully configure NSR? (Choose two.)

- A. You should configure the max period for NSR precision timers.
- B. You must configure GRES.
- C. You must configure graceful restart.
- D. You should configure commit synchronization.

ANSWER: A B**QUESTION NO: 2**

Exhibit

```
(edit)
user@switch# show interfaces ge-0/0/1
native-vlan-id 20;
unit 0 {
  family ethernet-switching {
    interface-mode trunk;
    vlan {
      members [ 10 20 ];
    }
  }
}
```

Referring to the exhibit, what will happen to untagged frames?

- A. The untagged frames are dropped.
- B. The untagged frames are load balanced between VLAN 10 and VLAN 20.
- C. The untagged frames are associated with VLAN 10.
- D. The untagged frames are associated with VLAN 20.

ANSWER: A

QUESTION NO: 3

Which statement describes integrated routing and bridging (IRB) interfaces?

- A. An IRB interface is an IP gateway for hosts of a bridge domain.
- B. An IRB interface assigns interfaces to VLANs.
- C. An IRB interface enables Layer 2 switching on the router.
- D. An IRB interface defines a bridge domain.

ANSWER: C

QUESTION NO: 4

Which two LSA types are permitted in OSPF totally stubby areas? (Choose two.)

- A. Type 1
- B. Type 3
- C. Type 5
- D. Type 7

ANSWER: C D

QUESTION NO: 5

Which statement is correct about IS-IS?

- A. IS-IS is a distance vector routing protocol.
- B. IS-IS is a path vector routing protocol.
- C. IS-IS is a link-state routing protocol.
- D. IS-IS is a classful routing protocol.

ANSWER: C

QUESTION NO: 6

Which BGP attribute is used to detect routing loops?

- A. AS path
- B. MED
- C. local preference
- D. next hop

ANSWER: A

QUESTION NO: 7

What are two bridging concepts that are used to maintain an Ethernet switching table? (Choose two.)

- A. learning
- B. exporting
- C. aging
- D. timing

ANSWER: A

QUESTION NO: 8

You are asked to create connections between routing instances on the same Junos device and route between the connected instances. What are two ways to accomplish this task? (Choose two.)

- A. Use physical interfaces.
- B. Use an IRB interface.
- C. Use logical tunnel interfaces.
- D. Use loopback interfaces.

ANSWER: A B

QUESTION NO: 9

Exhibit

```
[edit]
user@router# show interfaces ge-0/0/0
unit 0 {
  family bridge {
    interface-mode trunk;
    vlan-id-list 101-120;
  }
}
[edit]
user@router# show interfaces ge-0/0/1
flexible-vlan-tagging;
unit 0 {
  vlan-id 200;
  family bridge {
    interface-mode trunk;
    inner-vlan-id-list 101-120;
  }
...
[edit]
user@router# show bridge-domains
...
[edit]
user@router# show bridge-domains
bd {
  vlan-id-list 101-120;
}
```

Referring to the exhibit, which two statements are correct? (Choose two.)

- A. Traffic ingressing ge-0/0/0 that is tagged with VLAN 101 will egress ge-0/0/1 unchanged.
- B. Traffic ingressing ge-0/0/0 that is tagged with VLAN 100 will be dropped.
- C. Traffic ingressing ge-0/0/0 that is tagged with VLAN 200 will egress ge-0/0/1 with an outer VLAN tag of 200.
- D. Traffic ingressing ge-0/0/0 that is tagged with VLAN 101 will egress ge-0/0/1 with an outer VLAN tag of 200.

ANSWER: A B

QUESTION NO: 10

What are three well-known mandatory BGP attributes? (Choose three.)

- A. next hop
- B. origin
- C. community
- D. MED
- E. AS path

ANSWER: A B E