

DUMPS ARENA

HCIA-Video Conference V3.0

Huawei H11-851 V3.0

Version Demo

Total Demo Questions: 20

Total Premium Questions: 544

Buy Premium PDF

<https://dumpsarena.co>

sales@dumpsarena.co

sales@dumpsarena.co
dumpsarena.co

QUESTION NO: 1

MCU cascading methods include automatic cascading and manual cascading. ()

- A. True
- B. False

ANSWER: A

QUESTION NO: 2

Remote video loopback, loopback video stream through the far end of the codec processing. ()

- A. True
- B. False

ANSWER: B

QUESTION NO: 3

Is the following description of a multi-stream hybrid meeting correct? ()

- A. In SVC mode, each terminal only sends a small full-screen code stream to the MCU, and after the MCU receives the code stream, according to the viewing needs of each venue, the received code stream is decoded, reduced, and spliced, and each code stream is finally sent to the venue that needs to be watched.
- B. CloudMCU and VP98 series MCUs support multi-stream hybrid conferencing.
- C. Multi-stream hybrid conferencing supports access to SVC conference terminals and MCU conference terminals.
- D. In AVC mode, each terminal sends multiple streams of different sizes to the MCU, and after the MCU receives the stream, it will receive multiple streams of different sizes in different venues according to the viewing needs of each venue. Forward directly to the venue for viewing multiple screens at the same time.

ANSWER: A B C D

QUESTION NO: 4

Before the meeting, you need to routinely check the status of the terminal input source, which includes ().

- A. Video input source
- B. USB interface

- C. IdeaShare
- D. Audio input source

ANSWER: A C D

QUESTION NO: 5

SIP is an abbreviation for Session Initialization Protocol and is used for initialization.)), altering and terminating sessions of one or more participants, including multimedia conferencing, video, network calls,

etc. ().

- A. True
- B. False

ANSWER: A

QUESTION NO: 6

() Only unmanageable additions to SMC2.0 are supported.

- A. TE10
- B. P3206
- C. Box300
- D. RP100

ANSWER: A

QUESTION NO: 7

On the Call Status page of the TE terminal, the information that can be queried is ().

- A. Video Rate
- B. Audio Rate
- C. Video Frame Rate
- D. Audio Protocol

ANSWER: A B C D

QUESTION NO: 8

The following is the dual-stream protocol that is ().

- A. H225
- B. H245
- C. H239
- D. BFCP

ANSWER: C

QUESTION NO: 9

SMC3.0 supports multi-user role management, where the system administrator has () permissions.

- A. Device management
- B. Users issue
- C. with meeting rooms Meeting management
- D. System Configuration

ANSWER: A B C D

QUESTION NO: 10

The SMC supports adding a network address book on the GK, which is stored on the FTP server. ()

- A. True
- B. False

ANSWER: A

QUESTION NO: 11

() The message indicates that the request cannot be implemented on any SIP server.

- A. 6xx
- B. 5xx
- C. 1xx
- D. 3xx

ANSWER: A

QUESTION NO: 12

In the server settings on TE Mobile, the IP address of the registered server is the address of the SIP server, and the port number is typically 5060 ()

- A. True
- B. False

ANSWER: A

QUESTION NO: 13

The business boards for mcUs of the 321.96XX series include ().

- A. GCCA
- B. GPUX
- C. Media
- D. ISDN

ANSWER: B C D

QUESTION NO: 14

The MCU node number after the meeting, consisting of () and ().

- A. MCU prefix
- B. Subconference No.
- C. Service area code
- D. Venue Number

ANSWER: A B

QUESTION NO: 15

The video output of TE40, the output GUI interface is ().

- A. Video output 1

- B. Video output 2
- C. Video output 3
- D. S-video

ANSWER: A B C

QUESTION NO: 16

In IdeaHub's whiteboard interface, the whiteboard content can be erased by means of ().

- A. Finger Erase
- B. One-click Screen Clearing
- C. Palm Erase
- D. Fist Erase

ANSWER: A B C D

QUESTION NO: 17

The main indicator that describes the clarity of the video is the resolution, and the main indicator that describes the fluency of the video is the frame rate. ()

- A. True
- B. False

ANSWER: A

QUESTION NO: 18

() can provide media exchange, video codec functions.

- A. 96 Series MCUs
- B. 98 MCU
- C. CloudMCU
- D. SMC

ANSWER: A B C

QUESTION NO: 19

The 338.96XX family of MCUs can be upgraded using ().

- A. Built-in web upgrade
- B. Command line upgrade
- C. USB upgrade
- D. SMC Management Interface Upgrade

ANSWER: A B D

QUESTION NO: 20

The number of meetings required for automatic cascading is ().

- A. 1
- B. 2
- C. 3
- D. 4

ANSWER: A